

CAT. NO. KLN-02-2011

D SOLV RUST

Rust Remover

D-SOLV RUST is a liquid blend of acids, surfactant, inhibitors and other chemicals. It is formulated to remove mild, thin rust from steel and other ironmongery.

APPLICATIONS

Rust removal from steel works and other ironmongery.

DIRECTIONS FOR USE

Apply **D-SOLV RUST** by brush onto the rusted surface liberally. Allow the rust remover to stand for 20 minutes until the foaming action subsides. After this period, clean the surface with water and steel brush until rust is removed.

For light rust stains, **D-SOLV RUST** can be diluted with water at the rate of 1 part **D-SOLV RUST** and 1part clean water.

PACKING

D-SOLV RUST is packed in 4 and 20 liter pails.

COVERAGE

10 - 12 square meters per liter (Concentrated).

HEALTH AND SAFETY

D-SOLV RUST contains acids. Always use rubber gloves, and eye goggles when using the product. If accidentally spilled on the skin, wash immediately with water. If ingested seek medical attention immediately.

Revised: 15.01.2023

Technical information, data are to be considered as typical values and not sales specification. Actual measured values may vary due to factors beyond our control. Indications concerning function and application of the products are empirical. Although the information is believed to be accurate, there is no warranty by ISOLA. None of the recommendations becomes part of the warranted quality of the products. Due to the fact that the conditions of individual use are beyond ISOLA's direct and continuous control, ISOLA disclaims all responsibility in connection with the use of its products and does not warrant against any loss direct or consequential

ISOLA SOLUTIONS W.L.L

P.O. Box 530, Manama, Kingdom of Bahrain, Tel: 17784777, Fax:17911422, Email: isola@hajihassan.com, web: www.isolasolutions.com