

CAT. No. ST-10-2010

# ISOMOULD

## Release Agent

**ISOMOULD** is a special blend of mineral oils and chemical additives and designed for use for quick easy stripping of concrete formwork. It is non-staining and contains rust inhibitor to protect metal form from corrosion and preservative to increase the life of wood forms. **ISOMOULD** promotes a water repellent interface between concrete and formwork resulting in a smooth, flat, unstained surface. Its air release property minimizes formation of air voids and blemishes.

### ADVANTAGES

- Minimize voids, blemishes and defects on concrete surface.
- Quick, easy and clean release of concrete from formworks.
- Non-staining; will not transfer from forms.
- With built-in rust inhibitor and wood preservative extending life of forms.

### DIRECTION FOR USE

Hardened concrete adhering to old forms should be removed, **ISOMOULD** is directly applied to the formworks by brush or spray. On new wood forms, apply two coats of **ISOMOULD** allowing first coat to saturate the wood completely.

Depending on method of application and composition of forms, **ISOMOULD** will cover from 20 to 60 square meters per liter. Avoid excessive application and puddling.

### PACKING

**ISOMOULD** is packed in 20-liter pail and 200- liter drum.

### CAUTION

**ISOMOULD** contains solvents. Keep away containers from naked flames.

### SHELF LIFE

Twelve months minimum in original stored in warehouse condition below 32<sup>0</sup> Celsius ambient temperatures.

### HEALTH / SAFETY

Always wear eye protection and rubber hand gloves when handling. Accidental splashes to the eyes should be flushed with plenty of water. If irritation persist, consult a physician. Accidental splashes to the skin should be washed with water and soap. For more information, refer to MSDS.

Revised: 15.01.2023

Technical information, data are to be considered as typical values and not sales specification. Actual measured values may vary due to factors beyond our control. Indications concerning function and application of the products are empirical. Although the information is believed to be accurate, there is no warranty by ISOLA. None of the recommendations becomes part of the warranted quality of the products. Due to the fact that the conditions of individual use are beyond ISOLA's direct and continuous control, ISOLA disclaims all responsibility in connection with the use of its products and does not warrant against any loss direct or consequential

**ISOLA SOLUTIONS W.L.L**

P.O. Box 530, Manama, Kingdom of Bahrain, Tel: 17784777, Fax:17911422, Email: [isola@hajihassan.com](mailto:isola@hajihassan.com), web: [www.isolasolutions.com](http://www.isolasolutions.com)

**An ISO 9001: 2015 Certified Company**

